



Overview

HP RPS1600 Redundant Power System

Models

HP RPS1600 Redundant Power System

JG136A

Product overview

HP RPS1600 Redundant Power System (JG136A)

Ports	8 redundant power supply ports	
	Restrictions: two -56V/25A DC(PoE); six -56V/8A DC(non-PoE)	
Physical characteristics	Dimensions	17.32(w) x 15.63(d) x 1.74(h) in (44 x 39.7 x 4.42 cm)
	Weight	14.11 lb (6.4 kg)
	Full configuration weight	16.75 lb (7.6 kg)
	Operating temperature	14°F to 122°F (-10°C to 50°C)
Environment	Operating relative humidity	5% to 95%
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 95%
	Altitude	up to 13,123 ft (4 km)
	Acoustic	Pressure: 53 dB; ISO 7779, ISO 9296
Electrical characteristics	Voltage	100-120/200-240 VAC
	Current	30/60 A
	Idle power	38 W
	Maximum power rating	3550 W
	RPS power	3200 W
	PoE power	2800 W
	RPS	-55 V
	PoE	-55 V
	Frequency	50/60 Hz
	Notes	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. With one RPS1600 Power Supply, the PRS1600 Redundant Power System can provide 1600W power output; With two PRS1600 Power Supplies, the output power is 3200W.
Safety	CE Labeled; UL 60950-1; IEC 60950-1; ICES-003; FCC Part 15, Subpart B; EU RoHS Compliant; EN 60950-1/A11; C-Tick; VCCI Class A; ROHS Compliance; EN 300386	
Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

HP RPS1600 Redundant Power System accessories

Power Supply

HP RPS1600 1600W AC Power Supply	JG137A
----------------------------------	--------

Power cords

HP X290 1000 A JD5 2m RPS Cable	JD187A
HP X290 1000 A JD5 Non-PoE 2m RPS Cable	JD188A
HP X290 1000 B JD5 2m RPS Cable	JD189A

To learn more, visit: www.hp.com/networking

Copyright 2012 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.