

HPE Synergy Interconnect Link Cable

QuickSpecs

Unified Interconnect Solution

Connection between HPE Virtual Connect SE 100Gb F32 Module for Synergy and HPE Synergy 50Gb Interconnect Link Module

HPE Synergy Interconnect Link Cables

Connection between HPE Virtual Connect SE 100Gb F32 Module for Synergy and HPE Synergy 50Gb Interconnect Link Module

Platform Information

Models

HPE Synergy 300Gb Interconnect Link 2.1m Direct Attach Copper Cable	876680-B21
The following three SKUs all comply to the Low Smoke Zero Halogen (LSZH) standard and refers to the behavior of chemical compounds when combusted - specifically the quantity of smoke generated and the toxicity of the emissions.	
HPE Synergy 300Gb Interconnect Link 3m Active Optical Cable	876689-B21
HPE Synergy 300Gb Interconnect Link 5m Active Optical Cable	876692-B21
HPE Synergy 300Gb Interconnect Link 15m Active Optical Cable	876698-B21

The following three SKUs are all Plenum-Rated, referring to its special insulation that has low smoke and low flame characteristics.

HPE Synergy 300Gb Interconnect Link 3m Plenum Rated Active Optical Cable	P64635-B21
HPE Synergy 300Gb Interconnect Link 5m Plenum Rated Active Optical Cable	P64638-B21
HPE Synergy 300Gb Interconnect Link 15m Plenum Rated Active Optical Cable	P64641-B21

Notes:

- Mixing LSZH and Plenum-Rated cables in the same Logical Enclosure (LE) is not supported.
- Since the Plenum-Rated cables are newer, they require a minimum version of OneView and a minimum firmware version on the modules that they are connecting - VC 100Gb F32 Switch module and the 50G ICM Satellite module.
 - OneView version must be OV 9.0 or higher
 - VC 100Gb F32 Switch must have firmware of 2.7.0 or higher
 - 50Gb ICM Satellite that has Spare Part Number 879437-001 or P02747-001 must have firmware of 1.2.1.0 or higher
 - 50Gb ICM Satellite that has Spare Part Number P57815-001 or P57838-001 must have firmware of 2.0.2.0 or higher
 - The firmware versions for the VC 100Gb F32 Switch and the 50Gb ICM Satellite modules are part of the SSP SY2024.07.01

Warning: If non-supported firmware is used with Plenum cables, creation of the Logical Enclosure will fail. Customers must upgrade all firmware on connecting modules before installing the Plenum-Rated cables.

Ensure that OneView and the modules that these cables are connecting have supported firmware before starting any replacement or growth operations with Plenum-Rated cables.

Check the HPE OneView for Synergy version number. If you are not running HPE OneView for Synergy version 9.0 or later, update the software. See the [HPE OneView for Synergy User Guide Document - HPE OneView for HPE Synergy Firmware and](#)

[Driver Update Guide | HPE Support](#) for details on updating the software.

Update the firmware on the connecting modules. See the [HPE OneView for Synergy User Guide Document - HPE OneView for HPE Synergy Firmware and Driver Update Guide | HPE Support](#) for details on updating the firmware.

Standard Features

At a Glance Features

- EU RoHS-6 and China RoHS compliant
 - Supports 25Gb/s per lane
 - Twelve-channel full-duplex active optical cable
-

Service and Support

HPE Services

No matter where you are in your digital transformation journey, you can count on HPE Services to deliver the expertise you need when, where and how you need it. From planning to deployment, ongoing operations and beyond, our experts can help you realize your digital ambitions.

<https://www.hpe.com/services>

Consulting Services

No matter where you are in your journey to hybrid cloud, experts can help you map out your next steps. From determining what workloads should live where, to handling governance and compliance, to managing costs, our experts can help you optimize your operations.

<https://www.hpe.com/services/consulting>

HPE Managed Services

HPE runs your IT operations, providing services that monitor, operate, and optimize your infrastructure and applications, delivered consistently and globally to give you unified control and let you focus on innovation.

[HPE Managed Services | HPE](#)

Operational services

Optimize your entire IT environment and drive innovation. Manage day-to-day IT operational tasks while freeing up valuable time and resources. Meet service-level targets and business objectives with features designed to drive better business outcomes.

<https://www.hpe.com/services/operational>

HPE Complete Care Service

HPE Complete Care Service is a modular, IT environment service designed to help optimize your entire IT environment and achieve agreed upon IT outcomes and business goals through a personalized experience. All delivered by an assigned team of HPE Services experts. HPE Complete Care Service provides:

- A complete coverage approach
- An assigned HPE team
- Modular and fully personalized engagement
- Enhanced Incident Management experience with priority access
- Digitally enabled and AI driven customer experience

<https://www.hpe.com/services/completecare>

HPE Tech Care Service

HPE Tech Care Service is the operational support service experience for HPE products. The service goes beyond traditional support by providing access to product specific experts, an AI driven digital experience, and general technical guidance to not only reduce risk but constantly search for ways to do things better. HPE Tech Care Service delivers a customer-centric, AI driven, and digitally enabled customer experience to move your business forward. HPE Tech Care Service is available in three response levels. Basic, which provides 9x5 business hour availability and a 2-hour response time. Essential which provides a 15-minute response time 24x7 for most enterprise level customers, and Critical which includes a 6-hour repair commitment where available and outage management response for severity 1 incidents.

<https://www.hpe.com/services/techcare>

HPE Lifecycle Services

HPE Lifecycle Services provide a variety of options to help maintain your HPE systems and solutions at all stages of the product lifecycle. A few popular examples include:

- Lifecycle Install and Startup Services: Various levels for physical installation and power on, remote access setup, installation and startup, and enhanced installation services with the operating system.
- HPE Firmware Update Analysis Service: Recommendations for firmware revision levels for selected HPE products, taking into account the relevant revision dependencies within your IT environment.
- HPE Firmware Update Implementation Service: Implementation of firmware updates for selected HPE server, storage, and solution products, taking into account the relevant revision dependencies within your IT environment.
- Implementation assistance services: Highly trained technical service specialists to assist you with a variety of activities, ranging from design, implementation, and platform deployment to consolidation, migration, project management, and onsite technical forums.
- HPE Service Credits: Access to prepaid services for flexibility to choose from a variety of specialized service activities, including assessments, performance maintenance reviews, firmware management, professional services, and operational best practices.

Notes: To review the list of Lifecycle Services available for your product go to:

<https://www.hpe.com/services/lifecycle>

For a list of the most frequently purchased services using service credits, see the [HPE Service Credits Menu](#)

Other Related Services from HPE Services:

HPE Education Services

Training and certification designed for IT and business professionals across all industries. Broad catalogue of course offerings to expand skills and proficiencies in topics ranging from cloud and cybersecurity to AI and DevOps. Create learning paths to expand proficiency in a specific subject. Schedule training in a way that works best for your business with flexible continuous learning options.

<https://www.hpe.com/services/training>

Defective Media Retention

An option available with HPE Complete Care Service and HPE Tech Care Service and applies only to Disk or eligible SSD/Flash Drives replaced by HPE due to malfunction.

Consult your HPE Sales Representative or Authorized Channel Partner of choice for any additional questions and service options.

Parts and Materials

HPE will provide HPE-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product QuickSpecs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

How to Purchase Services

Services are sold by Hewlett Packard Enterprise and Hewlett Packard Enterprise Authorized Service Partners:

- Services for customers purchasing from HPE or an enterprise reseller are quoted using HPE order configuration tools.
- Customers purchasing from a commercial reseller can find services at <https://ssc.hpe.com/portal/site/ssc/>

AI Powered and Digitally Enabled Support Experience

Achieve faster time to resolution with access to product-specific resources and expertise through a digital and data driven customer experience

Sign into the HPE Support Center experience, featuring streamlined self-serve case creation and management capabilities with inline knowledge recommendations. You will also find personalized task alerts and powerful troubleshooting support through an intelligent virtual agent with seamless transition when needed to a live support agent.

<https://support.hpe.com/hpesc/public/home/signin>

Consume IT On Your Terms

[GreenLake](#) is the cloud delivering a unified platform experience that allows enterprises to simplify IT, reduce costs, and transform faster.

- Get faster time to market
- Save on TCO, align costs to business

- Scale quickly, meet unpredictable demand
- Simplify IT operations across your data centers and clouds

To learn more about HPE Services, please contact your Hewlett Packard Enterprise sales representative or Hewlett Packard Enterprise Authorized Channel Partner. Contact information for a representative in your area can be found at "Contact HPE"

<https://www.hpe.com/us/en/contact-hpe.html>

For more information, refer to: <http://www.hpe.com/services>

Technical Specifications

HPE Synergy 300G Interconnect Link 2.1m Direct Attach Copper Cable (876680- B21)	Connectivity	Length	6.89 ft. (2.1 m)
	Physical characteristics	Weight	1.46 lb.
	Environment	Operating temperature	32°F to 158°F (0°C to 70°C)
		Operating relative humidity	0% to 80%, noncondensing
		Non-operating/Storage temperature	-4°F to 185°F (-20°C to 85°C)
		Altitude	0-10,000 ft
	Electrical characteristics	Power consumption	1 watt maximum
	Notes:	Electrical Properties – Cable Characteristic Impedance: 90~115ohm – Crosstalk between pairs: 32dB max – Time delay: 1.6 nsec/ft. Total Latency 11nsec – BER: 10^{-12}max Physical Properties – Minimum Cable Bend Radius: 35.6 mm – Minimum Cable Bend Space: 86.4 mm	

HPE Synergy 300G Interconnect Link 3m Active Optical Cable (876689-B21)	Connectivity	Length	9.8ft. (3 m)
	Physical characteristics	Weight	0.5 lb.
	Environment	Operating temperature	32°F to 158°F (0°C to 70°C)
		Operating relative humidity	0% to 85%, noncondensing
		Non-operating/Storage temperature	-40°F to 185°F (-40°C to 85°C)
		Altitude	0-10,000ft
	Electrical characteristics	Power consumption	7.2 watts maximum
	Notes:	Electrical Properties – Time delay: 13.1 nsec/ft – BER: 10^{-12}max Physical Properties – Cable Diameter: 3.8 mm – Minimum Cable Bend Radius: 38 mm	

HPE Synergy 300G Interconnect Link 5m Active Optical Cable (876692-B21)	Connectivity	Length	16.4 ft. (5 m)
	Physical characteristics	Weight	0.5 lb.
	Environment	Operating temperature	32°F to 158°F (0°C to 70°C)
		Operating relative humidity	0% to 85%, noncondensing
		Non-operating/Storage temperature	-40°F to 185°F (-40°C to 85°C)
		Altitude	0-10,000ft

	Electrical characteristics	Power consumption	7.2 watts maximum
	Notes:	Electrical Properties – Time delay: 21.5 nsec/ft – BER: 10^{-12}max Physical Properties – Cable Diameter: 3.8 mm – Minimum Cable Bend Radius: 38 mm	

HPE Synergy 300G Interconnect Link 15m Active Optical Cable (876698-B21)	Connectivity	Length	49.2 ft. (15 m)
	Physical characteristics	Weight	0.5 lb.
	Environment	Operating temperature	32°F to 158°F (0°C to 70°C)
		Operating relative humidity	0% to 85%, noncondensing
		Non-operating/Storage temperature	-40°F to 185°F (-40°C to 85°C)
		Altitude	0-10,000ft
	Electrical characteristics	Power consumption	7.2 watts maximum
	Notes:	Electrical Properties – Time delay: 63.5 nsec/ft – BER: 10^{-12}max Physical Properties – Cable Diameter: 3.8 mm – Minimum Cable Bend Radius: 38 mm	

HPE Synergy 300G Interconnect Link 3m Plenum Rated Active Optical Cable (P64635-B21)	Connectivity	Length	9.8ft. (3 m)
	Physical characteristics	Weight	0.5 lb.
	Environment	Operating temperature	32°F to 158°F (0°C to 70°C)
		Operating relative humidity	0% to 85%, noncondensing
		Non-operating/Storage temperature	-40°F to 185°F (-40°C to 85°C)
		Altitude	0-10,000ft
	Electrical characteristics	Power consumption	7.2 watts maximum
	Notes:	Electrical Properties – Time delay: 13.1 nsec/ft – BER: 10^{-12}max Physical Properties – Cable Diameter: 3.8 mm – Minimum Cable Bend Radius: 38 mm	

HPE Synergy 300G Interconnect Link 5m Plenum Rated Active Optical Cable (P64638-B21)	Connectivity	Length	16.4 ft. (5 m)
	Physical characteristics	Weight	0.5 lb.
	Environment	Operating temperature	32°F to 158°F (0°C to 70°C)
		Operating relative humidity	0% to 85%, noncondensing
		Non-operating/Storage temperature	-40°F to 185°F (-40°C to 85°C)
		Altitude	0-10,000ft
	Electrical characteristics	Power consumption	7.2 watts maximum
	Notes:	Electrical Properties – Time delay: 21.5 nsec/ft – BER: 10^{-12}max	

	Physical Properties		
	– Cable Diameter: 3.8 mm – Minimum Cable Bend Radius: 38 mm		
HPE Synergy 300G Interconnect Link 15m Plenum Rated Active Optical Cable (P64641-B21)	Connectivity	Length	49.2 ft. (15 m)
	Physical characteristics	Weight	0.5 lb.
	Environment	Operating temperature	32°F to 158°F (0°C to 70°C)
		Operating relative humidity	0% to 85%, noncondensing
		Non-operating/Storage temperature	-40°F to 185°F (-40°C to 85°C)
		Altitude	0-10,000ft
	Electrical characteristics	Power consumption	7.2 watts maximum
	Notes:	Electrical Properties – Time delay: 63.5 nsec/ft – BER: 10⁻¹²max Physical Properties – Cable Diameter: 3.8 mm – Minimum Cable Bend Radius: 38 mm	

Environment friendly Products and Approach - End-of life Management and Recycling

Hewlett Packard Enterprise offers end-of-life [product return, trade-in, and recycling programs](#), in many geographic areas, for our products. Products returned to Hewlett Packard Enterprise will be recycled, recovered or disposed of in a responsible manner. The European Union Waste Electrical and Electronic Equipment Directive [EU WEEE] (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the [Hewlett Packard Enterprise web site](#). These instructions may be used by recyclers and other WEEE treatment facilities as well as Hewlett Packard Enterprise OEM customers who integrate and re-sell Hewlett Packard Enterprise equipment.

Summary of Changes

Date	Version History	Action	Description of Change
02-Feb-2026	Version 9	Changed	Document updated to comply with FY26 rebranding.
05-Aug-2024	Version 8	Updated	Platform Information section was updated. Removed OBS SKUs and added Plenum rated SKUs
04-Dec-2023	Version 7	Changed	Service and Support Section was updated
15-Nov-2021	Version 6	Updated	Service and Support Section was updated
18-Jan-2021	Version 5	Updated	Overview Section was updated
03-Sep-2019	Version 4	Updated	Models Section was updated
05-Feb-2018	Version 3	Changed	Technical Specifications section was updated.
31-Mar-2016	Version 2	Changed	Overview and Technical Specifications sections were updated.
		Added	SKUs added in Overview section: 804095-B21, 804098-B21, 804155-B21, 804155-B21, 804101-B21, 804104-B21, 804107-B21, 804110-B21
1-Dec-2015	Version 1	Created	New QuickSpecs

Copyright

[Chat now](#)

© Copyright 2026 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

c04815247 - 15425 - Worldwide - V9 - 02-February-2026
HEWLETT PACKARD ENTERPRISE
HPE.com

